product details

64250 HLX 20W 6V G4 ESB FS1

Product description:	64250 HLX 20W 6V G4 ESB FS1
Product code:	4050300012407
Quantity:	Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300012407

Applications	
Burning position	any

Categorizations	
Sstl-Number	4739543
ANSI code	ESB
LIF	M/30

General Description	
Base (standard designation)	G4

Logistical Data	
Product weight	1.170 g

Technical - Electrical Data	
Construction voltage	6 V
Lamp voltage	6.0 V
Rated wattage	20 W

Technical - Geometries	
Diameter	9 mm
Filament length	2.30 mm
Light centre length (LCL)	19.5 mm
Illuminated field	2.3*0.8 mm²
Length	31 mm
Filament diameter	0.8 mm

Technical - Lifespan	
Lifespan	100 h

Technical - Light Technical Data	
Luminous flux	460 lm

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300012407	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	3,600 g (0,000 g)	0,040 Cubic dec.
4050300890999	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	190,500 g (0,000 g)	1,864 Cubic dec.

Some lamp models are available as XENOPHOT versions (type HLX).
With xenon instead of krypton as the filler gas, a luminous flux up to 10 % higher is achieved with the same electrical lamp data.

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH